



# White Grease

## Product description

White Grease is a high-grade lubricant based on PTFE for the treatment of metal and plastic parts.

## Properties

- Lubricates
- Reduces friction and wear
- Rust and corrosion-resistant
- Water-repellent
- Does not contain silicones
- In and outdoor use
- Does not drip

## Applications

- Ideal for turning and moving parts of metal and plastic.
- Features dual effect: atomizes as oil and has creep properties on the one hand, it solidifies as fat and has a good adhesion and good pressure resistance on the other hand.
- Suitable for vertical applications, does not flow down or drip.
- To be used for machines, roller bearings, axles, cogwheels, conveyer belts, rubber gasket profiles,...



## Technical data

Base	Mineral oil with white lithium soap and PTFE
Consistency	Liquid
Density	ca. 0.72 g/ml
Application temperature	+5°C → +35°C
Temperature resistance	-20°C → +120°C
Volatile organic compounds (VOC)	80%
Drop point	>180°C

## Substrates

- Substrate condition  
Clean, free of dust and grease.
- Substrate types  
All types of metals and plastics.

## Application method

- Application method  
Surfaces must be cleaned, degreased and dry. Shake can well before use. Spray at a distance of appr. 20 cm of the object. To obtain the best result apply the spray while the moving parts are in motion if possible.



# White Grease

## Health- and Safety Recommendations

Dangerous. Respect the precautions for use.

In case of contact with eyes, wash immediately with plenty of water.

Use only in well-ventilated areas.

## Packaging/Logistics

Colour: White

Packaging: 400 ml aerosol

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.