



# Cleaner & Degreaser

## Product description

Cleaner & Degreaser is a powerful quick-drying cleaner and degreaser for various maintenance and assembly jobs.

## Properties

- Cleans and degreases
- Aerosol can be used in any angle (360°)
- Fast drying
- Leaves no residue

## Applications

- Removal of uncured MS, PU, silicone sealants, tar residue, grease, wax,...
- Substrate preparation before sealing and adhering.

## Technical data

Base	Hydrocarbon solvents
Consistency	Liquid
Density	ca. 0.75 g/ml
Acidity level	Neutral
Application temperature	+5°C → +35°C
Volatile organic compounds (VOC)	97 %
Solubility in water	Not soluble



## Substrates

- Substrate condition  
Clean, free of dust and grease.
- Substrates  
All types of metals and plastics.

## Application method

- Application method  
Shake can well before use. Spray at a distance of approx. 20 cm of the object. Apply as required. After applying rub the surface dry with a clean towel. Always rub in one direction. Test for adverse effects on the surface in advance.

## Health- and Safety Recommendations

Use only in well-ventilated areas.  
In case of contact with eyes, wash immediately with plenty of water.  
Dangerous. Respect the precautions for use.

## Packaging/Logistics

Colour: Transparent  
Packaging: 400 ml aerosol



# Cleaner & Degreaser

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

## Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.