



Adhesive Remover

Product description

Adhesive Remover is a transparent solvent mixture suitable for removing fresh glue stains and for the cleaning and degreasing of metal surfaces.

Properties

- Removes fresh glue stains
- Leaves no residue
- Cleans and degreases
- Fast drying
- Aerosol can be used in any angle (360°)

Applications

- Transparent solvent mixture suitable for removing fresh glue stains and cleans brushes, palette knives and glue spatulas.
- Removes hard excess contact glue.
- Powerful cleaner and degreaser of metals substrates. Also suitable for the preparation of surfaces for the application of sealants or adhesives.
- Not suitable for polystyrene and Plexiglas.



Technical data

Base	Mixture based on low boiling solvents
Consistency	Liquid
Density	Ca. 0.85 g/ml
Viscosity	1 mPa.s
Application temperature	5°C → 30°C
Volatile organic compounds (VOC)	97%
Solubility in water	Not soluble

Application method

- Application method
Shake can well before use. Spray at a distance of approx. 20 cm of the object. Apply as required. After applying rub the surface dry with a clean towel. Always rub in one direction. Test for adverse effects on the surface in advance.

Health- and Safety Recommendations

Dangerous. Respect the precautions for use.
In case of contact with eyes, wash immediately with plenty of water.
Use only in well-ventilated areas.

Packaging/Logistics

Colour: Transparent
Packaging: 400 ml aerosol
Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C



Adhesive Remover

Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.