



Cockpit Maintenance Spray

Product description

High-end silicone-free cockpit spray for protection and maintenance of the dashboard in cars.

Properties

- Does not contain silicones
- Aerosol can be used in any angle (360°)
- Cleans
- After application it leaves a lemon scent
- Anti-static and saving continual dusting
- Protects

Applications

- This spray is suitable for all types of plastic and provides optimum care.
- Ideal to freshen up the colors, leaving a matt appearance.
- Prevents parts from squeaking and cracking.
- Designed to provide a lasting protection against ageing and to stop the material becoming brittle.



Technical data

Base	Mixture based on paraffin oil
Consistency	Liquid
Application temperature	+5°C → +35°C

Substrates

- Substrate types
Cockpit Maintenance Spray is compatible with following substrates: metal, plastics, rubbers. We recommend a preliminary adhesion and compatibility test on every surface.
- Suitable substrates
metal plastics rubbers

Application method

- Application method
Shake the can well before use and spray at a distance of appr. 20 cm of the surface. Apply as required. After applying, rub the surface dry with a clean towel.

Health- and Safety Recommendations

In case of contact with eyes, wash immediately with plenty of water.

Dangerous. Respect the precautions for use.

Use only in well-ventilated areas.

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.

Packaging/Logistics

Colour: Transparent

Packaging: 400 ml aerosol



Cockpit Maintenance Spray

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.