



Cutting Oil

Product description

Cutting Oil is a high quality oil which prevents overheating of metals when cutting and drilling.

Properties

- Reduces friction and wear
- Excellent cooling characteristics
- Good anti-mist properties prevents unwanted oil mist
- Aerosol can be used in any angle (360°)
- Does not contain silicones
- Non corrosive

Applications

- Reduces resistance against cutting and mechanical tension of cutting tools.
- Suitable for: drilling, milling, cutting, sawing, filing, tapping, turning, planning and punching of steel and most ferrous and non-ferrous metals.



Technical data

Base	Mixture based on mineral oil
Consistency	Liquid
Density	Ca. 0,89 g/ml
Viscosity	3115-3560 mPa.s
Flashpoint	≥ 200°C
Volatile organic compounds (VOC)	20%
Solubility in water	Not soluble

Application method

- Application method
Shake can well before use. Spray tools and materials abundantly before tooling. It is important that both tools and the material are covered with lubricant at all time.

Health- and Safety Recommendations

Dangerous. Respect the precautions for use.
In case of contact with eyes, wash immediately with plenty of water.
Use only in well-ventilated areas.

Packaging/Logistics

Colour: Transparent
Packaging: 400 ml aerosol
Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C



Cutting Oil

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.