



# Degrip All

## Product description

Degrip All is a high quality penetrating oil which dissolves rust and corrosion.

## Properties

- Aerosol can be used in any angle (360°)
- In and outdoor use
- Protects
- Rust and corrosion-resistant
- High capacity of penetration.

## Applications

- Highly efficient in releasing corroded and rusted metal parts such as nuts, bolts and machine parts.
- To be used on screws, bolts, nuts, moving parts, axles, hinges, chains, garden tools, etc...
- Due to the very low surface tension Degrip All penetrates into very small openings to release stuck parts.



## Technical data

Base	Mixture based on mineral oil
Consistency	Liquid
Density	ca. 0,69 g/ml
Viscosity	1 mPa.s
Application temperature	+5°C → +35°C
Flashpoint	52°C
Volatile organic compounds (VOC)	84%
Solubility in water	Not soluble

## Substrates

- Substrate types  
Metals

## Application method

- Application method  
Remove dirt and loose rust mechanically by means of a metal brush. Shake can well before use. Spray sufficient product from a distance. Apply as required. Leave to penetrate during ca 5-10 minutes. Repeat if necessary.

## Health- and Safety Recommendations

Use only in well-ventilated areas.

In case of contact with eyes, wash immediately with plenty of water.

Dangerous. Respect the precautions for use.

## Packaging/Logistics

Colour: Transparent

Packaging: 400 ml aerosol



# Degrip All

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.